

KS951NXE2

Product family: Hood
Subfamily: Decorative wall hood
Aesthetics: Linea
Design: T flat
Width category: 90cm
Extraction: Expulsion
Electronic control
Material: Stainless steel
Color: Steel / Glass Frame
Type of steel: Brushed
EAN code: 8017709257316
Hood width: 90 cm



Aesthetics

Glass Type: Black
 Logo: Embossed

Controls

Control setting: Touch control
 Led color: Ice
 Display

Programs / Functions

No. of speeds: 3
 Intensive speed
 24h air filter function
 Time-setting options: Automatic switch-off

Technical Features

No. of lights: 2
 Light type: LED
 Light Power: 1 W
 Dimmer mode
 Free outlet maximum capacity: 820 m³/h
 Motor power: 275 W
 No. of filters: 3
 Anti-grease filters: Stainless steel

Vent outlet: 150 mm
 Minimum distance from ELECTRIC hob: 650 mm
 Minimum distance from GAS hob: 650 mm
 Non return valve

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	311	55
Speed 2	401	61
Speed 3	534	66
Intensive speed	756	73

Accessories Included

Tube reduction

Performance / Energy Label

Annual Efficiency Consumption (AEChood): 65.5 KWh/year
 Energy efficiency class (EEC): B
 Fluid Dynamic Efficiency (FDE): 27.5
 Fluid Dynamic Efficiency class (FDEC): B
 Lighting Efficiency (LE): 105
 Lighting Efficiency Class (LEC): A
 Grease Filtering Efficiency (GFE): 81.1 %
 Grease Filtering Efficiency Class (GFEC): C
 Air flow at minimum speed (Qmin): 311 m³/h
 Air flow at maximum speed (Qmax): 534 m³/h
 Air flow at boost speed (Qboost): 756 m³/h
 Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 55 dB(A)
 Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 66 dB(A)
 Airborne acoustical A-weighted sound power emission at

boost speed (SPEboost): 73 dB(A)
 Power Consumption in Off mode (Po): 0.49 W
 Time increase factor (F): 1.00
 Energy Efficiency Index per first cavity: 58.6
 Measured air flow rate at best efficiency point (Qbep): 393 m³/h
 Measured air pressure at best efficiency point (Qbep): 437 Pa
 Measured electric power input at best efficiency point (Wbep): 174 W
 Normal Power of the light system (Wl): 2 W
 Average illumination of the light on the cooking surface (Emiddle): 231
 Sound power level at highest setting (Lwa): 66 dB(A)

Electrical Connection


Electrical connection rating: 278 W
 Voltage: 220-240 V
 Frequency (Hz): 50-60 Hz
 Power supply cable length: 1500 mm

Accessories not included



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



KITFC161

Charcoal filters Kit 2 pieces

