

# KT110PE

Product family: Hood  
Subfamily: Decorative wall hood  
Aesthetics: Victoria  
Design: Chimney  
Width category: > 90cm  
Extraction: Expulsion  
Material: Painted material  
Color: Cream  
Type of steel: Brushed  
EAN code: 8017709211707  
Hood width: 110 cm



## Aesthetics

Logo: Applied

## Controls

Control setting: Control knobs  
No. of controls: 2  
Control knobs: Victoria  
Controls colour: Steel effect

## Programs / Functions

No. of speeds: 3  
Intensive speed

## Technical Features

No. of lights: 2  
Light type: LED  
Light Power: 1 W  
Light color temperature scale (°K): 3000 °K  
Free outlet maximum capacity: 820 m³/h  
Motor power: 275 W  
No. of filters: 4  
Anti-grease filters: Aluminium

Vent outlet: 150 mm  
Minimum distance from ELECTRIC hob: 650 mm  
Minimum distance from GAS hob: 750 mm  
Non return valve

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	326	49
Speed 2	439	57
Speed 3	554	63
Intensive speed	784	71

## Performance / Energy Label

Annual Efficiency Consumption (AEChood): 56.9 KWh/year

Energy efficiency class ( EEC): A



Fluid Dynamic Efficiency (FDE): 31.1  
Fluid Dynamic Efficiency class (FDEC): A  
Lighting Efficiency (LE): 83.2  
Lighting Efficiency Class (LEC): A  
Grease Filtering Efficiency (GFE): 69.2 %  
Grease Filtering Efficiency Class (GFEC): D  
Air flow at minimum speed (Qmin): 326 m³/h  
Air flow at maximum speed (Qmax): 554 m³/h  
Air flow at boost speed (Qboost): 784 m³/h  
Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 49 dB(A)  
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 63 dB(A)  
Airbourne acoustical A-weighted sound power emission at

boost speed (SPEboost): 71 dB(A)  
Energy Efficiency Index per first cavity: 52.2  
Measured air flow rate at best efficiency point (Qbep): 413 m³/h  
Measured air pressure at best efficiency point (Qbep): 456 Pa  
Measured electric power input at best efficiency point (Wbep): 168 W  
Normal Power of the light system (WI): 2 W  
Average illumination of the light on the cooking surface (Emiddle): 183  
Sound power level at highest setting (Lwa): 63 dB(A)

### Electrical Connection

Electrical connection rating: 278 W  
Voltage: 220-240 V  
Frequency (Hz): 50-60 Hz  
Power supply cable length: 1000 mm

### Also available

Alternative colours available: White, Black, Stainless steel  
Available colours: KT110BE-KT110BLE - KTR110XE

### Accessories not included



**FLT6**  
Round Charcoal filters (kit 2 pieces)



**KITALLFC**  
Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

