

SF4390MX

Product Family: Oven Category: 45cm compact Power supply: Electric Heat source: Electric Cooking method: Microwave with grill Oven control: Electronic EAN code: 8017709193546



Aesthetics

Aesthetics: Classic Design: Flat Colour: Fingerproof Stainless Steel Material: Stainless steel Type of steel: Brushed Glass Type: Eclipse Serigraphy colour: Black Serigraphy type: Symbols

Programs / Functions

No. of cooking functions: 5

Traditional cooking functions



Microwave functions



Other functions



Controls

Display technology: LCD Display generation: 1st Control setting: Control knobs No. of controls: 2 Control knobs: Classic Controls colour: Steel effect Door: With 2 horizontal strips Handle: Classic Handle Colour: Stainless steel Logo: Embossed



Options

Timer: Electronic Time-setting options: Delay start and automatic end cooking Minute minder End of cooking acoustic alarm Limited Power Consumption Mode Controls Lock / Child Safety

Technical Features

Temperature control: Electronic Minimum Temperature: 50 °C Maximum temperature: 250 °C Cavity material: Ever clean Enamel No. of shelves: 3 Shelves type: Metal racks Tiliting grill No. of lights: 1 Light type: Halogen Light Power: 40 W Light when door is opened Grill element - power: 1500 W Door: Temperate door

Performance / Energy Label

Net volume of the cavity: 40 litres No. of cavities: 1 Gross volume: 50 litres Microwave effective power: 1000 W

Accessories Included

Grid with back stop: 1 Special baker plate: 1

Electrical Connection

Voltage: 220-240 V Electrical connection rating (W): 3300 W Current: 15 A Frequency (Hz): 50 Hz

Power supply cable length: 115 cm

Accessories not included



BN620-1 Enamelled tray, 20mm deep

BN640 Enamelled tray, 40mm deep



BNP608T Teflon-coated tray, 8mm depth, to be placed on the grid



BVG Glass tray and stainless steel grid, 40mm deep Total no. of door glasses: 3 No. of thermoreflecting door glasses: 2 Soft Close hinges Safety Thermostat Heating suspended when door is opened Cooling system: Tangential Microwave screen protection Microwave stops when door is opened Usable cavity space dimensions (HxWxD): 212x462x407 mm

Other options: Eco light, Quick start Showroom demo option





GT1P-2

Partially extractable telescopic guides (1 level) for ovens with metal frames. Length: 355.5 mm, extraction: 285 mm. Material: Stainless steel AISI 430 polished.



GT1T-2

Totally extractable telescopic guides (1 level) for ovens with metal frames. Length: 355.5 mm, extraction: 418.5 mm. Material: Stainless steel AISI 430 polished.



KIT330X Trim kit for 45 cm Classica ovens

KP43M



Suitable for microwave ovens and combination microwave ovens. To install KP43M a technical intervention is required. As the kit is intended for MWO ovens, for safety reasons the substitution of the door can be performed just by a qualified personell



PR3845X

PIR2

Antifingerprint stainless steel. Cover for furniture in column installation of more ovens

Steel pan with grid, glass top, not suitable for ovens with telescopic guides



SFLK1

Child lock



SMOLD

Set of 7 silicone moulds for ice creams, ice lollies, pralines, ice cubes or to portion food. Usable from -60°C to +230°C

