

KI120XE

Product family: Hood
Subfamily: Decorative island hood
Aesthetics: Neutral
Design: T flat
Width category: > 90cm
Extraction: Expulsion
Electronic control
Material: Stainless steel
Color: Stainless steel
Type of steel: Brushed
EAN code: 8017709204051
Hood width: 120 cm



Aesthetics

Logo: Embossed

Controls

Control setting: Electronic buttons
 Led color: White

Programs / Functions

No. of speeds: 3
 Intensive speed
 Time-setting options: Automatic switch-off

Technical Features

No. of lights: 4
 Light type: LED
 Light Power: 1 W
 Light color temperature scale (°K): 4000 °K
 Free outlet maximum capacity: 820 m³/h
 Motor power: 275 W
 No. of filters: 4
 Anti-grease filters: Aluminium

Filter replacement indicator
 Vent outlet: 150 mm
 Minimum distance from ELECTRIC hob: 650 mm
 Minimum distance from GAS hob: 750 mm
 Non return valve

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	316	48
Speed 2	385	59
Speed 3	529	62
Intensive speed	783	70

Accessories Included

Tube reduction

Performance / Energy Label

Annual Efficiency Consumption (AEChood): 63.6 KWh/year
 Energy efficiency class (EEC): B
 Fluid Dynamic Efficiency (FDE): 28.7
 Fluid Dynamic Efficiency class (FDEC): A
 Lighting Efficiency (LE): 70.9
 Lighting Efficiency Class (LEC): A
 Grease Filtering Efficiency (GFE): 79.8 %
 Grease Filtering Efficiency Class (GFEC): C
 Air flow at minimum speed (Qmin): 316 m³/h
 Air flow at maximum speed (Qmax): 529 m³/h
 Air flow at boost speed (Qboost): 783 m³/h
 Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 48 dB(A)
 Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 62 dB(A)
 Airborne acoustical A-weighted sound power emission at

boost speed (SPEboost): 70 dB(A)
 Power Consumption in Off mode (Po): 0.71 W
 Time increase factor (F): 1.00
 Energy Efficiency Index per first cavity: 58.7
 Measured air flow rate at best efficiency point (Qbep): 394 m³/h
 Measured air pressure at best efficiency point (Qbep): 449 Pa
 Measured electric power input at best efficiency point (Wbep): 171 W
 Normal Power of the light system (WI): 4 W
 Average illumination of the light on the cooking surface (Emiddle): 312
 Sound power level at highest setting (Lwa): 62 dB(A)

Electrical Connection

Electrical connection rating: 279 W
 Voltage: 220-240 V
 Frequency (Hz): 50-60 Hz
 Power supply cable length: 1500 mm

Accessories not included



FLT6
 Round Charcoal filters (kit 2 pieces)

